



Ordering Information

Catalog No.	Finishes	Track Mountings	Luminaires	Lamp
83B70EWH 83B70EBK 83B70EAL	Matte White Matte Black Metallic Aluminum	All Lytespan® Track Systems and Multi-point. DO NOT USE with any other mounting accessories, stem mounted Radius® Track, ProSpec® Track or ATOM® systems. Can be wall mounted.	Use one of: 8313 83W4 8314 83W6 8316 83W7 8317 8318	70W Ceramic Metal Halide

Features

- Housing:** .10" thick extruded aluminum body with die cast end caps.
- Track Attachment Fitting:** Molded polycarbonate; rotates into track, integral polarity key guard.
- Brass Contact:** Extends for connection to second circuit in Advent Lytespan track.
- Safety Locking Lever:** Locks and supports module in track.
- On/Off Switch:** Rocker switch to disconnect power to the ballast.
- Power Receptacle:** 5kv rated, insulated. Accepts power connector from fixture.
- Integral Track Groove:** To mount PowerArc™ Modular spots and wall wash fixtures.

Electrical

Electronic Ballast
Input Voltage: 120V, 60Hz
Power Factor: > 0.99
Input Power: 77W
Max. Input Current: 0.64A
Total Harmonic Distortion: <5%
ANSI Code: M139, M143, M98
 Do not use on dimming circuit.

Finish

All painted finishes are baked enamel.

Labels

UL, cUL

Patents

Products shown here are protected by applicable patents and patents pending.

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2008 Philips Group • D1108